



GEOGULF2021

A U S T I N
October 27–29, 2021



Southern Arkansas CO₂-EOR and Saline Storage Assessment

D. Riestenberg, W. Wallace, G. Koperna, and K. Gray

ABSTRACT

This study evaluated the potential to revitalize several depleted southern Arkansas oil fields and improve the State's declining oil production while simultaneously storing CO₂. Advanced Resources International, Inc.'s oil field database was analyzed using reservoir and economic models to determine the potential for CO₂-EOR in terms of oil recovery and potential CO₂ demand. Of the 39 large oil reservoirs evaluated in southern Arkansas, 13 met the criteria for miscible CO₂-EOR. EOR modeling results predict 280 million barrels of potential oil recovery, requiring a CO₂ demand of 1980 BCF. This purchased CO₂ volume, equivalent to 104 million metric tons, is ultimately stored in the oil reservoirs. Further, shallow and/or heavy oil reservoirs may be candidates for EOR, given the successful 1970s–1980s demonstration of immiscible CO₂-EOR in the Lick Creek oilfield. In addition to EOR, there are multiple stacked saline reservoirs with the capacity to store CO₂ unassociated with oil recovery. The highest capacity candidate for CO₂ saline storage is likely the Reynolds oolitic limestone, in the Smackover formation, due to its excellent reservoir characteristics and overlying anhydrite seal (Buckner formation). The reservoir exhibits a maximum porosity of 26% and an average permeability of 1500 millidarcies. It has an estimated storage capacity of 1.2 to 3.2 million metric tons of CO₂ per square mile. Together, the considerable CO₂-EOR potential, saline reservoir storage capacity and industrial CO₂ sources increase the viability of carbon capture, utilization, and storage in southern Arkansas.

NOTES
